

Dependable Power on Demand

Built to deliver dependable grid power on demand, EDEN is a 2.5kWh mobile power station designed for the most demanding users in the film, TV, and outdoor industries. With its rugged, dustproof, and waterproof build, EDEN provides reliable AC and DC power anywhere you go. Rapid recharging, multiple output options, and silent operation ensure that your devices stay powered, and your creativity flows uninterrupted. Experience the freedom of continuous, versatile grid power anywhere with EDEN.



- Chemistry: Lithium-Ion
- LCD Screen: Realtime performance and diagnostics
- IP-65 rated
- AC Input: 100~250VAC, 50-60 Hz
- Solar DC Input: MPPT Nominal 36V
- AC Regulated output: 2 X 110VAC, 60Hz Pure Sine Wave
- DC Regulated Output: 2 X USB-C PD, 2 X USB-C
- Capacity: 2500Wh
- Fully charged in 4 hours
- Smart Electronic Fuses
- Silent Operation



Charge Fast, Create More

Cut down on downtime with EDEN's rapid recharging capabilities. Fully charge in 4 hours using a standard AC outlet or opt for eco-friendly solar charging when you're off the grid. Maximize your creative time without the constant worry of losing power.

Power Anything, Anywhere

Featuring two AC outlets and four USB-C ports, EDEN keeps all your essential devices running smoothly, from lights and cameras to craft and catering. Its lightweight design, practical handles, and silent operation make it perfect for any environment, from production sets to rugged outdoor locations. The large 3.3" color screen provides real-time diagnostics, so you're always in control.

Never Miss a Beat

EDEN functions as a seamless uninterruptible power supply (UPS), protecting your sensitive equipment from power outages. Whether you're shooting a critical scene or hosting an event, EDEN ensures your power flow remains uninterrupted, shifting smoothly from grid to battery power in an instant.





Battery Capacity	2500wh	Dimensions (W x H x D)	9.17in (233mm) x 18.39in (467mm) x 20.91in (531mm)
Chemistry	Lithium-lon	Output Ports	2 x Nema-5-20R2 X USB-C PD2 X USB-C (5v, 2a)
Charge Time (To full)	4 Hours	Voltage Outputs	• 2 X 110vac • 60hz Pure Sine Wave
Operating Temperature Range	14 To 140°F / -10 To 60°C	Fuse Protection	Smart electronic fuses
Weatherproof	IP65 Rated	Weight	64lbs / 29kg