

Laia T-Joy IP is the perfect IP camera controller for your conference rooms, auditoriums or churches where the quality of realization is paramount. In addition, thanks to its 4D Joystick you can control the viewing plane of your cameras.

## **Main characteristics**



Supports network and 2 analog control modes. Independent IP addresses in network mode



Supports VISCA, VISCA over IP, Onvif, PELCO-P and PELCO-D protocols



Software function control support for conference cameras



Variable speed 4D joystick control of cameras. Omnidirectional movements



Supports up to 7 camera shortcut control buttons for fast and easy operation













Av. Cerro del Águila, 3, 1B2. S.S. de los Reyes 28703 Madrid - Spain

## US Office:

2480 Presidential Way, unit 1104, West Palm Beach, FL. Main office number: 561-925-5242 US Toll Free: 844-513-1770

(\*) 6 years "Prime support" warranty for those products of the C-Pro, Broadcaster and Broadcaster Pro families by registering the purchase on Laia's website up to 2 months from the date of purchase.

## **Broadcaster t-Joy IP Specifications**: P/N: TJIP

## **Features**

Operating system: Linux

Protocol: VISCA, VISCA over IP, Onvif, PELCO-P, PELCO-D.

Interface: RS422, RS232, RJ45

Warning tone: Activate / deactivate beep when touching keys.

LCD screen: TFT LCD 320\*240

Power consumption: ≤5W

Power Supply: DC12V-2A

Working temperature:  $-10\sim55^{\circ}$ C /  $14^{\circ}$ F $\sim131^{\circ}$ F Storage temperature:  $-10^{\circ}$ C  $\sim60^{\circ}$ C /  $14^{\circ}$ F $\sim140^{\circ}$ F Dimension: 321.6mm X 179.2mm X 105.7mm

Weight: 1290g

