

AYRA PRO5

PROFESSIONAL ACTIVE TWO-WAY STUDIO MONITORS



Description

AYRA PRO5 studio monitor works perfectly in any listening environment, whether large or small production facilities, with absolute clarity. It delivers accurate monitoring and provides the engineer or producer with a neutral tool to analyze recordings and optimize the mix; for this reason, we call it PRO. Featuring a dedicated powerful internal DSP that optimizes frequency response and dynamics together with the exclusive RCF FiRPHASE processing and selected components, the AYRA PRO is the first Studio Monitor in its class to boast an outstanding 0° phase response.

Features

- > 50Hz 20kHz Frequency Response
- > 0° Phase Response
- > 75W + 25W Class-D Amplifiers
- > 5" Composite Fiberglass Woofer
- > 1" ferrofluid cooled Soft Dome tweeter
- > RCF Precision Waveguide
- > DSP Processing with FiRPHASE
- > Low distortion frontal Vented Ports

Part Number


13000597 AYRA PRO5	EU	90-240 V	Black - RAL 9005	EAN 8024530016890
13000644 AYRA PRO5	US	90-240 V	Black - RAL 9005	EAN 8024530017323
13000645 AYRA PRO5	UK	90-240 V	Black - RAL 9005	EAN 8024530017330
13000646 AYRA PRO5	JP	90-240 V	Black - RAL 9005	EAN 8024530017347



AYRA PRO5

PROFESSIONAL ACTIVE TWO-WAY STUDIO MONITORS

Line Art 2D



110 dB

4.3 kg / 9.48 lbs

TECHNICAL SPECIFICATIONS

Acoustical specifications

Frequency Response 50 Hz ÷ 20000 Hz

Max SPL @ 1m

Horizontal coverage angle 110°

Vertical coverage angle 70°

Transducers Dome Tweeter 1.0" neo, 1.0" v.c

Woofer 1 x 5.0", 1.0" v.c

Input/Output section | Input signal | bal/unbal

Input connectors XLR, Jack, RCA
Input sensitivity -2 dBu/+4 dBu

Processor sectionCrossover Frequencies2000Hz

Limiter Soft Limiter

Power sectionTotal Power200 W Peak, 100 W RMSHigh frequencies50 W Peak, 25 W RMS

Low frequencies 150 W Peak, 25 W RMS

Connections XLR, Jack, RCA

 Standard compliance
 Safety agency
 CE compliant

Weight

 Physical specifications
 Cabinet/Case Material
 MDF

 Size
 Black - RAL 9005

 Height
 300 mm / 11.81 inches

 Width
 185 mm / 7.28 inches

 Depth
 243 mm / 9.57 inches

Technical Specifications Page 2 of 2