

COMPACT M 10

TWO-WAY PROFESSIONAL SPEAKER



Description

COMPACT M 10 is a multipurpose two-way full-range speaker system, suitable for a wide range of applications. Its balanced sound is a big asset in near-field applications for the best intelligibility. The M 10 features high sensitivity, typical of professional audio cabinets thanks to the use of oversized magnets and a HI-FI sound quality, with smooth and wide frequency response, thanks to the wave-guided compression driver. The SPL level of low-distortion audio the M 10 can provide goes far beyond expectations of such a compact solution. The elegant and compact design with accurate finishing makes M 10 suitable for almost any environment, even with architectural constraints. Optional mounting accessories allow using M 10 on wall or ceiling installations.

Features

- > 300 W RMS power handling
- > 128 dB max SPL
- > 60 ÷ 20000 Hz frequency range
- > 90° x 70° constant directivity coverage angle
- > 1 x 10" high power woofer
- > 1 x 1.4" voice coil compression driver
- › High quality plywood cabinet
- > Steel front grille with clothing
- > Installation points available on rear, top and bottom panels
- > 4 pole EUROBLOCK connector (audio input and parallel link output)

Part Number


13000595 COMPACT M 10 13000723 COMPACT M 10 W Black - RAL 9005 EAN 8024530017804 White - RAL 9003 EAN 8024530019358



COMPACT M 10

TWO-WAY PROFESSIONAL SPEAKER

Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications

Frequency Response (-10dB) 60 Hz ÷ 20000 Hz

Max SPL @ 1m 128 dB 90° Horizontal coverage angle 70° Vertical coverage angle Directivity index Q 9 System Sensitivity 98 dB

Power section

Amplification Full Range Nominal Impedance 8 ohm 300 W Power Handling Peak Power Handling 1200 W PEAK

Protections Dynamic active mosfet

Crossover Frequencies 1800 Hz

Recommended Amplifiers XPS 16K, XPS 16KD, QPS 10K, QPS 6.0K, IPS 5.0K, IPS 2.5K, IPS

1.5K, DMA 504

Transducers Compression Driver 1 x 1.0", 1.4" v.c Woofer 1 x 10", 2.5" v.c

Input connectors Euroblock

Input/Output section Output connectors Euroblock Standard compliance Safety agency CE compliant

Physical specifications Cabinet/Case Material Plywood Hardware 8 x M8, 8 x M10 Grille Steel with clothing

> Color Black - RAL 9005, White - RAL 9003

Size Height 510 mm / 20.08 inches

Width 295 mm / 11.61 inches Depth 325 mm / 12.8 inches Weight 17 kg / 37.48 lbs

ACCESSORIES

H-BR 007 13360551 Rigging / Mounting 8024530021641

Technical Specifications Page 2 of 3



COMPACT M 10

TWO-WAY PROFESSIONAL SPEAKER

Rigging / Mounting	H-BR 007	13360604	8024530021658
	H-BR 2X COMPACT M 10	13360444	8024530018276
	H-BR 2X COMPACT M 10	13360463	8024530019563
	SWM-BR NC	13360199	8024530007355
	V-BR 007	13360552	8024530021726
	V-BR 007	13360606	8024530021733
	V-BR 2X COMPACT M 10	13360447	8024530018306
	V-BR 2X COMPACT M 10	13360466	8024530019587
Upgrade Kits	PNL IN-OUT AMPHENOL	12399063	8024530020149
	PNL IN-OUT SPEAKON	12399062	8024530018733

Technical Specifications Page 3 of 3