

MR 40

PAIR OF TWO-WAY SPEAKERS



Description

MR 40 is a bass-reflex two-way speaker designed to deliver uncompromised audio performance and high reliability in fixed installations. Blend in with any environment and deliver deep bass, smooth midrange, and finely-detailed high-frequency response. Quality components and careful acoustic design make the MR 40 the perfect speaker for listening in demanding applications. Suitable for indoor and outdoor installation.

Features

- > 40 W (8 ohm) power handling
- > 108 dB max SPL
- > 70 ÷ 20000 Hz frequency range
- > 110° x 100° coverage angles
- > 1 x 4" woofer (1" v.c.)
- > 1 x 1" dome tweeter (0.8" v.c.) neodymium magnet
- > Colour black RAL 9005 and white RAL 9003
- \rightarrow IP 55 protection grade
- > Swivel Wall mount accessory included
- > 4 pole EUROBLOCK connector

Part Number


13100034 MR 40 80hm 13100036 MR 40 W 80hm 


MR 40

PAIR OF TWO-WAY SPEAKERS

Line Art 2D









TECHNICAL SPECIFICATIONS

Acoustical specifications

Power section

Size

Frequency Response (-10dB) 70 Hz ÷ 20000 Hz

Max SPL @ 1m108 dBHorizontal coverage angle110°Vertical coverage angle100°Directivity index Q7

System Sensitivity 86 dB
Nominal Impedance 8 ohm
Power Handling 40 W

Peak Power Handling 160 W PEAK
Protections Bulb lamp
Crossover Frequencies 3000 Hz

Recommended Amplifiers DMA 504, DMA 162, DMA 82, DMA 162P

TransducersDome Tweeter1 x 1.0" neo, 0.8" v.cWoofer1 x 4.0", 1.0" v.c

 Input/Output section
 Input connectors
 Euroblock

 Output connectors
 Euroblock

 Standard compliance
 IP protection grade
 IP 55

Safety agency CE compliant

 Physical specifications
 Cabinet/Case Material
 Plastic

Hardware Wall mount bracket
Grille Aluminium

Color Black - RAL 9005, White - RAL 9003

 Height
 216 mm / 8.5 inches

 Width
 154 mm / 6.06 inches

 Depth
 135 mm / 5.31 inches

 Weight
 2.2 kg / 4.85 lbs

ACCESSORIES

 Rigging / Mounting
 MA 4
 13360367
 8024530014308

 MA 4
 13360368
 8024530014315

Technical Specifications Page 2 of 2