

# **MR 40T**

# PAIR OF TWO-WAY SPEAKERS WITH LINE TRANSFORMER



#### Description

MR 40T is a bass-reflex two-way speaker designed to deliver uncompromised audio performance and high reliability in fixed installations. Blend in with any environment and deliver deep bass, smooth midrange, and finely-detailed high-frequency response. Quality components and careful acoustic design make MR 40T the perfect speaker for listening in the most demanding applications. Suitable for indoor and outdoor installation.

#### **Features**

- > 40 W (8 ohm) / 20 W 10 W 5 W 2.5 W (70/100V) power handling
- > 108 dB max SPL
- > 70 ÷ 20000 Hz frequency range
- > 110° x 100° coverage angles
- > 1 x 4" woofer (1" v.c.)
- $\rightarrow$  1 x 1" dome tweeter (0.8" v.c.) neodymium magnet
- > Colour black RAL 9005 and white RAL 9003
- $\rightarrow$  IP 55 protection grade
- > Swivel wall mount accessory included
- > 4 pole EUROBLOCK connector

### Part Number

13100035 MR 40T 80hm 13100037 MR 40T W 80hm Black - RAL 9005 EAN 8024530017262 White - RAL 9003 EAN 8024530017279





# **MR 40T**

## PAIR OF TWO-WAY SPEAKERS WITH LINE TRANSFORMER

#### Line Art 2D









#### **TECHNICAL SPECIFICATIONS**

**Acoustical specifications** 

Power section

Frequency Response (-10dB) 70 Hz ÷ 20000 Hz

Max SPL @ 1m108 dBHorizontal coverage angle110°Vertical coverage angle100°Directivity index Q7System Sensitivity86 dB

Nominal Impedance 8 ohm
Power Handling 40 W
Peak Power Handling 160 W PEAK

Protections

Bulb lamp

Crossover Frequencies

3000 Hz

Recommended Amplifiers DMA 504, DMA 162, DMA 82, DMA 162P

TransducersDome Tweeter1 x 1.0" neo, 0.8" v.cWoofer1 x 4.0", 1.0" v.c

Input/Output section | Input connectors | Euroblock |
Output connectors | Euroblock |
Euroblock | Euroblock |
Euroblock | Euroblock |
Euroblock | Euroblock |

Constant Voltage Transformer 70/100 V
Power selection 1 20 W - 500 ohm

 Power selection 1
 20 W - 300 offm

 Power selection 2
 10 W - 1000 ohm

 Power selection 3
 5 W - 2000 ohm

 Power selection 4
 2.5 W - 4000 ohm

**Standard compliance** IP protection grade IP 55

Safety agency CE compliant
Physical specifications Cabinet/Case Material Plastic

Physical specificationsCabinet/Case MaterialPlasticHardwareWall mount bracket

Grille Aluminium

Color Black - RAL 9005, White - RAL 9003

Technical Specifications Page 2 of 3



# **MR 40T**

# PAIR OF TWO-WAY SPEAKERS WITH LINE TRANSFORMER

Size

 Height
 216 mm / 8.5 inches

 Width
 154 mm / 6.06 inches

 Depth
 135 mm / 5.31 inches

 Weight
 2.3 kg / 5.07 lbs

## **ACCESSORIES**

## Rigging / Mounting

MA 4 13360367 8024530014308 MA 4 13360368 8024530014315

Technical Specifications Page 3 of 3