



Description

MR 50 is a bass-reflex two-way speaker designed to deliver uncompromised audio performance and high reliability in fixed installations. Blend in with any environment and deliver deep bass, smooth midrange, and finely-detailed high-frequency response. Quality components and careful acoustic design make MR 50 the perfect speaker for listening in the most demanding applications. Suitable for indoor and outdoor installation.

Features

- > 60 W (8 ohm) power handling
- > 110 dB max SPL
- > 60 ÷ 20000 Hz frequency range
- > 110° x 100° coverage angles
- > 1 x 5" woofer (1" v.c.)
- \rightarrow 1 x 1" dome tweeter (0.8" v.c.) neodymium magnet
- > Colour black RAL 9005 and white RAL 9003
- \rightarrow IP 55 protection grade
- > Swivel wall mount accessory included
- > 4 pole EUROBLOCK connector

Part Number


13100038 MR 50 80hm 13100040 MR 50 W 80hm 


MR 50

PAIR OF TWO-WAY SPEAKERS

Line Art 2D









TECHNICAL SPECIFICATIONS

Acoustical specifications

Power section

Frequency Response (-10dB) 60 Hz ÷ 20000 Hz

Max SPL @ 1m

110 dB 110° Horizontal coverage angle 100° Vertical coverage angle 7 Directivity index Q

System Sensitivity 87 dB Nominal Impedance 8 ohm

Power Handling 60 W Peak Power Handling 240 W PEAK Protections Bulb lamp

Crossover Frequencies 3000 Hz

Recommended Amplifiers DMA 504, DMA 162, DMA 82, DMA 162P

Transducers Dome Tweeter 1 x 1.0" neo, 0.8" v.c Woofer 1 x 5.0", 1.0" v.c

Input/Output section Input connectors Euroblock

Output connectors Euroblock Standard compliance IP protection grade IP 55

Safety agency CE compliant **Physical specifications** Cabinet/Case Material Plastic

Hardware Wall mount bracket

Grille Aluminium

Black - RAL 9005, White - RAL 9003 Color Size

Height 270 mm / 10.63 inches Width 187 mm / 7.36 inches Depth 167 mm / 6.57 inches Weight 3.8 kg / 8.38 lbs

ACCESSORIES

MA 5 13360369 8024530014322 Rigging / Mounting MA 5 13360370 8024530014339

Technical Specifications Page 2 of 2